



US006674406B1

(12) **United States Patent**  
Tonn

(10) Patent No.: **US 6,674,406 B1**  
(45) Date of Patent: **Jan. 6, 2004**

(54) **MICROSTRIP PATCH ANTENNA WITH  
PROGRESSIVE SLOT LOADING**

(75) Inventor: **David A. Tonn, Charlestown, RI (US)**

(73) Assignee: **The United States of America as  
represented by the Secretary of the  
Navy, Washington, DC (US)**

(\*) Notice: **Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.**

(21) Appl. No.: **10/267,593**

(22) Filed: **Oct. 8, 2002**

(51) Int. Cl.<sup>7</sup> ..... **H01Q 1/38; H01Q 13/10**

(52) U.S. Cl. .... **343/700 MS; 343/770**

(58) Field of Search ..... **343/700 MS, 767,  
343/770, 792.5**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

**4,313,120 A \* 1/1982 Westerman ..... 343/771**

**4,518,967 A \* 5/1985 Westerman ..... 343/771**  
**5,400,042 A \* 3/1995 Tulintseff ..... 343/727**  
**5,977,924 A \* 11/1999 Takei et al. .... 343/770**  
**6,025,812 A \* 2/2000 Gabriel et al. .... 343/797**  
**6,388,621 B1 \* 5/2002 Lynch ..... 343/700 MS**

**\* cited by examiner**

**Primary Examiner—Tan Ho**

**(74) Attorney, Agent, or Firm—James M. Kasischke;  
Michael F. Oglo; Jean-Paul A. Nasser**

**(57) ABSTRACT**

A microstrip patch antenna with progressive slot loading is provided. A rectangular patch of electrically conductive material has a plurality of slots formed therein with each slot having its center aligned with the centerline of the patch's long dimension. Each slot further has its longitudinal axis perpendicular to the centerline. The slots are arranged in an order starting at a position  $n=1$  that is furthest from the patch's feedpoint so that, for an  $n$ -th slot, the inequalities  $L_n > L_{n+1}$  and  $W_n < W_{n+1}$  are always satisfied. In general, the length decreases linearly with each successive slot while the width increases exponentially with each successive slot.

**11 Claims, 1 Drawing Sheet**

